



ORDERING INFORMATION

U 6 F 05 E - C X X 2 - B
 (1)(2)(3) (4) (5) (6)(7)(8)(9) (10)

- SERIES NO.
U: USB CONNECTOR SERIES
- USB TYPE
6: MICRO.USB 5Pin
- USB MALE & FEMALE TYPE
F: FEMALE
- NUMBER OF PIN
05: 5 POSITIONS
- TAIL CONSTRUCTION TYPE
E: TERMINAL: SMD TYPE
SHELL: DIP TYPE
- HOUSING COLOR
C:COLOR:BLACK AND MATERIAL :LCP
- CONTACT PLATING
1: G/F 2: 5u'GOLD
3: 10u'GOLD 4: 15u'GOLD
5: 30u'GOLD 6: 3u'GOLD
- SHELL PLATING
N: NICKEL PLATING
T: TIN PLATING
G: Gold Plated
- PLASTIC ORIENTATION POST TYPE
1: WITH POST
2: WITHOUT POST
- B TYPE OR AB TYPE
B: B TYPE

ELECTRICAL

- Current rating: signal(pins 2,3,4): 1.0A;
power(pins 1,5): 1.8A
- Contact resistance:30 milliohms max
- Insulation resistance:1000 Megohms min
- Withstanding voltage:100V AC/minute
- Temperature range:-30°C to +85°C
- MARKED " * " SHOULD BE CONTROLLED BY QIP.

G	5.0				DRAWING:	GENERAL TOLERANCE			DESCRIPTION:	MICRO USB 5PIN B TYPE				
	4.0				Bains	.X:±0.10 .X*:±2° .XX:±0.05 .XX*:±1° .XXX:±0.02 .XXX*:±0.5°	UNIT: MM PROJECTION:							
H	3.0				CHECKED:	APPROVAL:	SCALE: 1/1		PART NO: U6F05E-CXT2-B	REV: 4.0				
	2.0				Tian Hai						Tian Hai	SHEET: 1/1	DRAWING NO: UK0132	SIZE: A4
	1.0													
	NO.	DATE	DESCRIPTION	APPROVAL										
	1		2	3	4	5	6	7	8					